ENGR 308 (Fall 2025) S. Alghunaim

8. Numerical integration

- differentiation and integration
- Newton-Cotes integration
- Trapezoidal method
- Simpson 1/3 & 3/8 rules
- Romberg integration

Derivatives


Difference approximation

$$\frac{\Delta y}{\Delta x} = \frac{f(x_i + \Delta x) - f(x_i)}{\Delta x}$$

Derivative

$$\frac{dy}{dx} = \lim_{\Delta x \to 0} \frac{f(x_i + \Delta x) - f(x_i)}{\Delta x}$$


• $\frac{dy}{dx}$ (also y' or $f'(x_i)$) is the slope of the tangent to the curve at x_i



• second derivative: $\frac{d^2y}{dx^2} = \frac{d}{dx} \left(\frac{dy}{dx} \right)$ measures how fast slope changes (*curvature*)

Equal-area graphical differentiation


- compute divided differences $\Delta y/\Delta x$
- plot as a step curve versus x
- sketch a smooth curve balancing positive and negative areas
- read dy/dx values from the smooth curve



Integration

Integration: the inverse process to differentiation written as

$$I = \int_{a}^{b} f(x) \, dx$$



- f(x) is the *integrand*
- \int is a stylized S symbolizing summation
- integral corresponds to area under the curve of f(x) between x = a and x = b
- definite integration: limits a, b specified
- indefinite integration: limits not specified, result is a family of functions

Relationship between differentiation and integration

differentiation and integration are inversely related processes

General link: integration

$$I = \int_{a}^{b} f(x) \, dx$$

is equivalent to solving the differential equation


$$\frac{dy}{dx} = f(x), \quad y(a) = 0$$


for y(b)

Example: if y(t) is position and v(t) is velocity, then

$$v(t) = \frac{d}{dt}y(t), \quad y(0) = 0$$

$$\iff y(t) = \int_0^t v(t) dt$$





Noncomputer methods for differentiation and integration

the function to be differentiated or integrated will usually be one of three forms:


- 1. simple continuous function (polynomial, exponential, trigonometric)
- 2. complicated continuous function (difficult or impossible to handle analytically)
- 3. tabulated function, values given at discrete points (e.g., experimental data)

Approaches

- for case 1: analytic calculus works well
- for cases 2 and 3: approximate methods must be employed


Graphical integration: grid method


- grid method: sum area of boxes under the curve
- finer grids → improved estimates



Graphical integration: strip method

- strip method: sum of rectangles area with height at strip midpoints
- finer strips → improved estimates





Outline

- differentiation and integration
- Newton-Cotes integration
- Trapezoidal method
- Simpson 1/3 & 3/8 rules
- Romberg integration

Newton-cotes formulas


replace a complicated function or data with an approximating polynomial:


$$I = \int_{a}^{b} f(x) dx \approx \int_{a}^{b} f_{n}(x) dx$$

where
$$f_n(x) = a_0 + a_1x + \dots + a_{n-1}x^{n-1} + a_nx^n$$

examples:

- the "strip method" corresponds to piecewise zero-order polynomials (constants)
- first-order polynomial: straight line connecting endpoints (trapezoidal rule)
- second-order polynomial: parabola (Simpson rule)
- straight line segments (composite trapezoidal rule)






Closed and open Newton-Cotes formulas

Closed form

- data points at the beginning and end of the limits of integration are known
- · commonly used for definite integration
- trapezoid and Simpson rules are closed forms

Open form

- integration limits extend beyond available data points
- · does not use endpoints
- mainly applied to improper integrals and in solving ordinary differential equations



Outline

- differentiation and integration
- Newton-Cotes integration
- Trapezoidal method
- Simpson 1/3 & 3/8 rules
- Romberg integration

Trapezoidal rule


use a first-order polynomial as the approximation:


$$I = \int_{a}^{b} f(x) dx \approx \int_{a}^{b} f_{1}(x) dx$$

ullet recall, Newton linear interpolation between (a,f(a)) and (b,f(b)) is

$$f_1(x) = f(a) + \frac{f(b) - f(a)}{b - a} (x - a)$$

the integral of the straight line approximation yields the trapezoidal rule:






Geometric interpretation of the trapezoidal rule

geometrically: $I_{\text{trap}} \approx \text{trapezoid}$ area formed by straight line connecting f(a), f(b)

from geometry, the area of a trapezoid is computed as




• in the trapezoidal rule, the trapezoid is rotated on its side, thus,

$$I_{\text{trap}} \approx \text{width} \times \text{average height} = (b - a) \frac{f(a) + f(b)}{2}$$

Trapezoidal method SA — ENGR308 8.12

Error of the trapezoidal rule

error can be substantial



• an estimate of the local truncation error for a single application of trapezoidal rule:

$$E_t = -\frac{1}{12}f''(\xi)(b-a)^3, \quad \xi \in [a,b]$$

- if f(x) is linear, then f''(x) = 0 and the trapezoidal rule is exact
- error will occur for functions with nonzero second derivatives (curvature)
- to estimate error, replace $f''(\xi)$ by average over interval:

$$E_a = -\frac{1}{12}\bar{f}''(x)(b-a)^3$$
, $\bar{f}''(x) = \frac{1}{b-a}\int_a^b f''(x)dx = \frac{f'(b)-f'(a)}{b-a}$

Trapezoidal method SA—ENGR308 8.13

Example

numerically integrate

$$f(x) = 0.2 + 25x - 200x^2 + 675x^3 - 900x^4 + 400x^5$$

from a = 0 to b = 0.8; the exact value of the integral is 1.640533

the function values are

$$f(0) = 0.2, \quad f(0.8) = 0.232$$

thus:

$$I_{\text{trap}} \approx 0.8 \times \frac{0.2 + 0.232}{2} = 0.1728$$

error:

$$E_t = 1.640533 - 0.1728 = 1.467733$$

percent relative error:

$$\varepsilon_t = 89.5\%$$

large error results because the straight line neglects much of the area above it

Example: approximate error estimate

- to estimate error, replace $f''(\xi)$ by average over interval $\frac{1}{a-b} \int_a^b f''(x) dx$
- · second derivative:

$$f''(x) = -400 + 4050x - 10800x^2 + 8000x^3$$

· average value:

$$\bar{f}''(x) = \frac{\int_0^{0.8} \left(-400 + 4050x - 10800x^2 + 8000x^3\right) dx}{0.8} = -60$$


approximate error:

$$E_a = -\frac{1}{12}(-60)(0.8)^3 = 2.56$$

- this is of the same order of magnitude and sign as the true error
- but not exact because \bar{f}'' is not necessarily equal to $f''(\xi)$

Multiple-application trapezoidal rule

divide interval [a,b] into n equal segments $[x_{i-1},x_i]$ and integrate each segment



Trapezoidal method SA—ENGR308 8.16

Composite trapezoidal rule

- consider n+1 equally spaced base points x_0, x_1, \ldots, x_n with stepsize $h=\frac{b-a}{n}$
- with $x_0 = a$ and $x_n = b$, the total integral is

$$I = \int_{x_0}^{x_1} f(x) \, dx + \int_{x_1}^{x_2} f(x) \, dx + \dots + \int_{x_{n-1}}^{x_n} f(x) \, dx$$

• substituting the trapezoidal rule for each integral yields

$$I_{\text{trap}} = \frac{h}{2} \Big[f(x_0) + f(x_1) \Big] + \frac{h}{2} \Big[f(x_1) + f(x_2) \Big] + \dots + \frac{h}{2} \Big[f(x_{n-1}) + f(x_n) \Big]$$

• grouping terms gives the composite trapezoidal rule:

$$I_{\text{trap}} = \frac{h}{2} \left[f(x_0) + 2 \sum_{i=1}^{n-1} f(x_i) + f(x_n) \right]$$

Error of the composite trapezoidal rule

summing the individual errors for each segment gives

$$E_t = -\frac{(b-a)^3}{12n^3} \sum_{i=1}^n f''(\xi_i)$$

where $f''(\xi_i)$ is the second derivative at a point ξ_i located in segment i

- result can be simplified by estimating the mean or value of second derivative
- for the entire interval as:

$$\frac{1}{n} \sum_{i=1}^{n} f''(\xi_i) \approx \bar{f}'' = \frac{1}{b-a} \int_{a}^{b} f''(x) dx = \frac{f'(b) - f'(a)}{b-a}$$

• therefore, $\sum f''(\xi_i) \approx n\bar{f}''$ and approximate error is

$$E_a = -\frac{(b-a)^3}{12n^2} \bar{f}''$$

• if the number of segments is doubled, the truncation error will be quartered

Example

use the two-segment trapezoidal rule to estimate

$$\int_0^{0.8} \left(0.2 + 25x - 200x^2 + 675x^3 - 900x^4 + 400x^5 \right) dx = 1.640533$$

• n = 2, h = (0.8 - 0)/2 = 0.4; function values:

$$f(0) = 0.2$$
, $f(0.4) = 2.456$, $f(0.8) = 0.232$

• apply rule:

$$I_{\text{trap}} = \frac{0.8}{4} [0.2 + 2(2.456) + 0.232] = 1.0688$$

· true error:

$$E_t = 1.640533 - 1.0688 = 0.57173, \quad \varepsilon_t = 34.9\%$$

• approximate error with $\bar{f}^{"}=-60$ (from page 8.15):

$$E_a = -\frac{0.8^3}{12(2)^2}(-60) = 0.64$$

Example

using n = 2, ..., 10, we get the result shown

\overline{n}	h	I_{trap}	ε_t (%)
2	0.4	1.0688	34.9
3	0.2667	1.3695	16.5
4	0.2	1.4848	9.5
5	0.16	1.5399	6.1
6	0.1333	1.5703	4.3
7	0.1143	1.5887	3.2
8	0.1	1.6008	2.4
9	0.0889	1.6091	1.9
10	0.08	1.6150	1.6

as n increases, error decreases, but at a gradual rate since $E_a \propto 1/n^2$

Trapezoidal rule with unequal segments

consider **unevenly spaced** segments $h_i = x_i - x_{i-1}$

the trapezoidal rule can be applied segment by segment:

$$I_{\text{trap}} = \frac{1}{2} \sum_{i=1}^{n} h_i \left(f(x_{i-1}) + f(x_i) \right)$$

$$= h_1 \frac{f(x_0) + f(x_1)}{2} + h_2 \frac{f(x_1) + f(x_2)}{2} + \dots + h_n \frac{f(x_{n-1}) + f(x_n)}{2}$$

- more practical since data (e.g., experimental measurements) are unevenly spaced
- same as multiple-application trapezoidal rule, except h_i not fixed
- cannot simplify as before, but easy to implement in computer code

Example: trapezoidal rule with unequal segments

use trapezoidal rule to integrate

$$f(x) = 0.2 + 25x - 200x^2 + 675x^3 - 900x^4 + 400x^5 = 1.640533$$

for data shown where the exact value of the integral is 1.640533

x	f(x)	X	f(x)
0.00	0.200000	0.44	2.842985
0.12	1.309729	0.54	3.507297
0.22	1.305241	0.64	3.181929
0.32	1.743393	0.70	2.363000
0.36	2.074903	0.80	0.232000
0.40	2.456000		

applying the formula gives


$$\begin{split} I_{\text{trap}} &= 0.12 \frac{1.309729 + 0.2}{2} + 0.10 \frac{1.305241 + 1.309729}{2} + \dots + 0.10 \frac{0.232 + 2.363}{2} = 1.594801 \\ \text{with error } \varepsilon_t &= \frac{1.640533 - 1.594801}{1.640533} \times 100\% = 2.8\% \end{split}$$

Outline

- differentiation and integration
- Newton-Cotes integration
- Trapezoidal method
- Simpson 1/3 & 3/8 rules
- Romberg integration

Simpson rules

- use higher-order polynomials to better approximate the integral
- for three points between f(a) and f(b), use parabola
- four points can be connected with a third-order polynomial



• resulting formulas of integrals under these polynomials are called Simpson rules

Simpson 1/3 & 3/8 rules SA — ENGR308 8.23

Simpson 1/3 rule

- we are given three equally spaced data points x_0, x_1, x_2 (two segments)
- Simpson 1/3 rule results when a 2nd-order interpolating polynomial is used

$$I = \int_{a}^{b} f(x) dx \approx \int_{a}^{b} f_{2}(x) dx$$

if $a = x_0$ and $b = x_2$, and $f_2(x)$ is represented by a 2nd Lagrange polynomial:

$$I \approx \int_{x_0}^{x_2} \left[\frac{(x-x_1)(x-x_2)}{(x_0-x_1)(x_0-x_2)} f(x_0) + \frac{(x-x_0)(x-x_2)}{(x_1-x_0)(x_1-x_2)} f(x_1) + \frac{(x-x_0)(x-x_1)}{(x_2-x_0)(x_2-x_1)} f(x_2) \right] dx$$

Simpson 1/3 rule: integrating yields

$$I_{1/3} = (b - a) \frac{f(x_0) + 4f(x_1) + f(x_2)}{6}$$
$$= \frac{h}{3} [f(x_0) + 4f(x_1) + f(x_2)]$$

where $h = \frac{b-a}{2}$ (note that the midpoint is $x_1 = \frac{a+b}{2}$)

Error of Simpson 1/3 rule

truncation error for one segment (with $h = \frac{b-a}{2}$):

$$E_t = -\frac{1}{90} h^5 f^{(4)}(\xi) = -\frac{(b-a)^5}{2880} f^{(4)}(\xi) \quad \text{for some } \xi \in (a,b)$$

- Simpson 1/3 rule is *third-order accurate* (error $\propto f^{(4)}$)
- i.e., rule exact for all cubic polynomials
- · approximate error for one segment

$$E_a = -\frac{(b-a)^5}{2880} \, \bar{f}^{(4)}, \quad \bar{f}^{(4)} = \frac{1}{b-a} \int_a^b f^{(4)}(x) dx = \frac{f^{(3)}(b) - f^{(3)}(a)}{b-a}$$

 $ar{f}^{(4)}$ is the average fourth derivative over the interval

Example

approximate

$$I = \int_0^{0.8} (0.2 + 25x - 200x^2 + 675x^3 - 900x^4 + 400x^5) dx = 1.640533$$

with
$$f(0) = 0.2$$
, $f(0.4) = 2.456$, $f(0.8) = 0.232$

• Simpson 1/3 rule:

$$I \approx I_{1/3} = (0.8) \frac{0.2 + 4(2.456) + 0.232}{6} = 1.367467$$

exact error:


$$E_t = I - I_{1/3} = 1.640533 - 1.367467 = 0.2730667 \quad (\varepsilon_t = 16.6\%)$$

· estimated error

$$-\frac{(b-a)^5}{2880}f^{(4)}(\xi)\approx E_a=-\frac{(0.8)^5}{2880}\left(-2400\right)=0.2730667$$

where -2400 is the average of $f^{(4)}$ on [0, 0.8]

Multiple-application Simpson 1/3 rule



- subdivide [a,b] into **even** number n of equal segments $h=\frac{b-a}{n}$
- integrate

$$I = \int_{x_0}^{x_2} f(x) dx + \int_{x_2}^{x_4} f(x) dx + \dots + \int_{x_{n-2}}^{x_n} f(x) dx$$

Simpson 1/3 & 3/8 rules SA—ENGR308 8.27

Composite Simpson 1/3 rule

applying Simpson 1/3 rule to each subinterval:

$$I_{1/3} = \frac{h}{3} \left[f(x_0) + 4f(x_1) + f(x_2) \right] + \frac{h}{3} \left[f(x_2) + 4f(x_3) + f(x_4) \right]$$

+ \dots + \frac{h}{3} \left[f(x_{n-2}) + 4f(x_{n-1}) + f(x_n) \right]

· combining terms and yields

$$I_{1/3} = \frac{h}{3} \left[f(x_0) + 4 \sum_{\substack{i=1 \\ i \text{ odd}}}^{n-1} f(x_i) + 2 \sum_{\substack{j=2 \\ j \text{ even}}}^{n-2} f(x_j) + f(x_n) \right]$$

where $h = \frac{b-a}{n}$

• method requires even number of segments (odd number of points)

Error of composite Simpson 1/3 rule

• approximate truncation is sum of errors and average over n/2 integrals:

$$E_a = -\frac{(b-a)^5}{180 n^4} \bar{f}^{(4)}$$

where

$$\bar{f}^{(4)} = \frac{1}{a-b} \int_{a}^{b} f^{(4)}(x) dx = \frac{f^{(3)}(b) - f^{(3)}(a)}{b-a}$$

is the average value of the fourth derivative of f(x) on [a,b]

• error decreases much faster than trapezoidal rule:

- trapezoidal: $E \sim O(n^{-2})$

- Simpson 1/3: $E \sim O(n^{-4})$

Example

use multiple application of Simpson 1/3 rule with n=4 to estimate the integral

$$f(x) = 0.2 + 25x - 200x^2 + 675x^3 - 900x^4 + 400x^5$$

from a = 0 to b = 0.8; exact (true) value: 1.640533

• for n = 4 (h = (0.8 - 0)/4 = 0.2):

$$f(0) = 0.2, \ f(0.2) = 1.288, \ f(0.4) = 2.456, \ f(0.6) = 3.464, \ f(0.8) = 0.232$$

· hence.

$$I_{1/3} = \tfrac{0.8}{12} \left[\, 0.2 + 4 (1.288 + 3.464) + 2 (2.456) + 0.232 \,\right] = 1.623467$$

true error and estimated error:

$$E_t = 1.640533 - 1.623467 = 0.017067,$$
 $\varepsilon_t = 1.04\%$

$$E_a = -\frac{(0.8)^5}{180(4)^4} (-2400) = 0.017067$$

Simpson 3/8 rule

use a third-order Lagrange polynomial to approximate integral:

$$I = \int_{a}^{b} f(x) dx \approx \int_{a}^{b} f_{3}(x) dx$$

require four points x_0, x_1, x_2, x_3 (n = 3 segments)

· resulting formula:

$$I_{3/8} = \frac{b-a}{8} \left[f(x_0) + 3f(x_1) + 3f(x_2) + f(x_3) \right]$$
$$= \frac{3h}{8} \left[f(x_0) + 3f(x_1) + 3f(x_2) + f(x_3) \right]$$

where $h = \frac{b-a}{3}$

· truncation error:

$$E_t = -\frac{3}{80}h^5 f^{(4)}(\xi) = -\frac{(b-a)^5}{6480}f^{(4)}(\xi), \quad E_a = -\frac{(b-a)^5}{6480}\bar{f}^{(4)}$$

slightly more accurate than Simpson 1/3 rule, but requires 4 points


8.31

Simpson 1/3 versus 3/8 rules

- Simpson 1/3 rule is usually the method of preference:
 - attains third-order accuracy with only 3 points
 - more efficient than 3/8 rule
- Simpson 3/8 rule requires 4 points and useful when the no. of segments is odd

Example: suppose we have 5 segments, then we have two options:

- multiple-application trapezoidal rule → large truncation error
- apply Simpson 1/3 rule to the first 2 segments and Simpson 3/8 rule to others



Simpson 1/3 & 3/8 rules 8.32

Example

numerically integrate

$$f(x) = 0.2 + 25x - 200x^2 + 675x^3 - 900x^4 + 400x^5$$
, $a = 0$, $b = 0.8$

using (a) Simpson 3/8 rule; (b) 5 segments used with Simpson 1/3 and 3/8 rules

(a) Simpson 3/8 rule with four equally spaced points ($h = \frac{0.8-0}{3} = 0.2667$)

$$f(0) = 0.2, \quad f(0.2667) = 1.432724,$$

 $f(0.5333) = 3.487177, \quad f(0.8) = 0.232$

yields

$$I_{3/8} \approx \frac{0.8}{8} [0.2 + 3(1.432724 + 3.487177) + 0.232] = 1.519170$$

$$E_t = 1.640533 - 1.519170 = 0.121363 \quad (\varepsilon_t = 7.4\%)$$

$$E_a = -\frac{(0.8)^5}{6480} (-2400) = 0.121363$$

(b) five-segment case $(h = \frac{0.8 - 0}{5} = 0.16)$

$$f(0) = 0.2,$$
 $f(0.16) = 1.296919,$ $f(0.32) = 1.743393,$ $f(0.48) = 3.186015,$ $f(0.64) = 3.181929,$ $f(0.80) = 0.232$

First two segments (Simpson 1/3 rule)

$$I_1 = \frac{0.32}{6} [0.2 + 4(1.296919) + 1.743393] = 0.380324$$

Last three segments (Simpson 3/8 rule)

$$I_2 = \frac{0.48}{8} [1.743393 + 3(3.186015 + 3.181929) + 0.232] = 1.264754$$

Total integral


$$\begin{split} I_{\text{total}} &= I_1 + I_2 = 0.380324 + 1.264754 = 1.645077 \\ E_t &= 1.640533 - 1.645077 = -0.004544 \quad (\varepsilon_t = -0.28\%) \end{split}$$

Example: combination of methods for uneven data

given the data below, use trapezoidal and Simpson rules where appropriate to find

$$\int_0^{0.8} f(x) = 0.2 + 25x - 200x^2 + 675x^3 - 900x^4 + 400x^5 dx$$

\boldsymbol{x}	f(x)	X	f(x)
0.00	0.200000	0.44	2.842985
0.12	1.309729	0.54	3.507297
0.22	1.305241	0.64	3.181929
0.32	1.743393	0.70	2.363000
0.36	2.074903	0.80	0.232000
0.40	2.456000		



Simpson 1/3 & 3/8 rules SA — ENGR308 8.35

Example: inclusion of Simpson rules for uneven data

- first segment (x = 0 to 0.12): trapezoidal rule $I_1 = 0.0906$
- next two segments (x = 0.12 to 0.32): Simpson 1/3 rule $I_2 = 0.2758$
- next three segments (x = 0.32 to 0.44): Simpson 3/8 rule $I_3 = 0.2727$
- next two segments (x = 0.44 to 0.64): Simpson 1/3 rule $I_4 = 0.6685$
- last two unequal segments: trapezoidal rule $I_5 = 0.1663 + 0.1298$

total integration:

$$I_{\text{total}} = I_1 + I_2 + I_3 + I_4 + I_5 = 1.603641 \implies \varepsilon_t = 2.2\%$$

Simpson 1/3 & 3/8 rules 8.36 — ENGR308 8.36

Outline

- differentiation and integration
- Newton-Cotes integration
- Trapezoidal method
- Simpson 1/3 & 3/8 rules
- Romberg integration

Romberg integration

- Romberg integration is based on successive applications of the trapezoidal rule
- but employs mathematical manipulations to achieve higher accuracy
- key idea: combine results from trapezoidal approximations with different stepsizes to reduce error

Romberg integration SA_ENGR308 8.37

Richardson extrapolation

suppose composite trapezoidal rule estimate is

$$I = I(h) + E(h), \qquad h = (b - a)/n$$

- -I(h) = approximation from an n-segment application of the trapezoidal rule
- -E(h) = truncation error
- for two estimates with stepsizes h_1 and h_2 ($h_2 < h_1$):

$$I(h_1) + E(h_1) = I(h_2) + E(h_2)$$

where error is

$$E(h) \approx -\frac{b-a}{12}h^2\bar{f}^{"}$$

ratio of errors:

$$\frac{E(h_1)}{E(h_2)} \approx \left(\frac{h_1}{h_2}\right)^2 \Rightarrow E(h_1) \approx \left(\frac{h_1}{h_2}\right)^2 E(h_2)$$

Error elimination and improved estimate

substituting and rearranging gives

$$E(h_2) \approx \frac{I(h_1) - I(h_2)}{1 - (h_1/h_2)^2}$$

gives estimate of truncation error in terms of integral estimates and stepsizes

improved estimate of the integral:

$$I \approx I(h_2) + E(h_2) = I(h_2) + \frac{1}{(h_1/h_2)^2 - 1} [I(h_2) - I(h_1)]$$

ullet estimate has error $O(h^4)$, versus $O(h^2)$ for trapezoidal rule

Special case: halved intervals

• if $h_2 = h_1/2$, the Romberg formula simplifies to

$$I \approx \frac{4}{3}I(h_2) - \frac{1}{3}I(h_1)$$

forms the basis of Romberg integration tables

before, we evaluated

$$\int_0^{0.8} \left(0.2 + 25x - 200x^2 + 675x^3 - 900x^4 + 400x^5\right) dx$$

by single and multiple applications of the trapezoidal rule, obtaining:

segments	h	integral	ε_t (%)
1	8.0	0.1728	89.5
2	0.4	1.0688	34.9
4	0.2	1.4848	9.5

use Richardson extrapolation with halved step ($h_2 = h_1/2$),

$$I \approx \frac{4}{3}I(h/2) - \frac{1}{3}I(h)$$

to compute improved estimates of the integral

combine 1- and 2-segment results

$$I \approx \frac{4}{3}(1.0688) - \frac{1}{3}(0.1728) = 1.367467$$

$$E_t = 1.640533 - 1.367467 = 0.273067 \quad (\varepsilon_t = 16.6\%)$$

• combine 2- and 4-segment results

$$I \approx \frac{4}{3}(1.4848) - \frac{1}{3}(1.0688) = 1.623467$$

$$E_t = 1.640533 - 1.623467 = 0.017067 \quad (\varepsilon_t = 1.0\%)$$

Takeaway

- a single Richardson step boosts the order from $O(h^2)$ (trapezoid) to $O(h^4)$
- significant accuracy gains with no extra function evaluations beyond two trap. runs

Romberg integration: higher-order error correction

• combine two $O(h^4)$ results $\Rightarrow O(h^6)$

$$I \approx \frac{16}{15}I_m - \frac{1}{15}I_l$$

- $-I_m$ = more accurate estimate
- $-I_1$ = less accurate estimate
- combine two $O(h^6)$ results $\Rightarrow O(h^8)$

$$I \approx \frac{64}{63}I_m - \frac{1}{63}I_l$$

Example

- ullet we used Richardson extrapolation to compute two integral estimates of $O(h^4)$
- ullet we can combine these estimates to compute an integral with $O(h^6)$

$$I \approx \frac{16}{15}(1.623467) - \frac{1}{15}(1.367467) = 1.640533$$

exact to seven significant figures

8.42

Romberg integration: general algorithm

$$I_{j,k} \approx \frac{4^{k-1}I_{j+1,k-1} - I_{j,k-1}}{4^{k-1} - 1}$$

- $I_{j,k}$ = improved integral with k=1: $I_{j,1}$ original trapezoid $O(h^2)$
- j = index distinguishing more (j + 1) and less (j) accurate integrals
- $k \ge 2$ level of accuracy $(k = 2: O(h^4), k = 3: O(h^6), ...)$


Stopping criterion: terminate when

$$|\varepsilon_a| = \left| \frac{I_{1,k} - I_{2,k-1}}{I_{1,k}} \right| \times 100\% < \varepsilon_s$$

Interpretation

- each iteration adds one trapezoidal estimate
- successively better integrals appear along the lower diagonal

Graphical depiction of Romberg integration



the first column contains the trapezoidal rule evaluations that are designated $I_{i,1}$

- $j = 1 \implies$ single-segment application (stepsize = b a)
- $j=2 \implies$ two-segment application (stepsize = $\frac{b-a}{2}$)
- $j = 3 \implies$ four-segment application (stepsize = $\frac{b-a}{4}$)
- and so forth

$$\int_0^{0.8} \left(0.2 + 25x - 200x^2 + 675x^3 - 900x^4 + 400x^5\right) dx$$

	O(h²)	O(h⁴)	O(h ⁶)	O(h ⁸)
(a)	0.172800 1.068800	1.367467		
(b)	0.172800 1.068800 — 1.484800 —	1.367467 1.623467	1.640533	
(c)	0.172800 1.068800 — 1.484800 — 1.600800	1.367467 1.623467 1.639467	1.640533 1.640533	1.640533

References and further readings

- S. C. Chapra and R. P. Canale. Numerical Methods for Engineers (8th edition). McGraw Hill, 2021. (Ch.21, 22)
- S. C. Chapra. Applied Numerical Methods with MATLAB for Engineers and Scientists (5th edition).
 McGraw Hill, 2023. (Ch.19, 20)

references SA_ENGR308 8.46